

### Key priority

---

lowglare


### material and Process

---


- anti water outdoor downlight
- with glare control design
- optional for round or square shape
- optional for color temperature
- workign temperature -20~50°C

# 防水筒灯


## Outdoor Downlight




Code	Watt(w)	Optic	Flux(lm)
ORDL100-15WA10	15W	10°	1185lm
ORDL100-15WA15	15W	15°	1495lm
ORDL100-15WA24	15W	24°	1502lm
ORDL100-15WA38	15W	38°	1439lm
ORDL100-15WA60	15W	60°	1396lm



Protection: IP65/IK07  
 Weight: 0.4KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo




Code	Watt(w)	Optic	Flux(lm)
ORDL136-25WA10	25W	10°	1937lm
ORDL136-25WA15	25W	15°	2496lm
ORDL136-25WA24	25W	24°	2502lm
ORDL136-25WA38	25W	38°	2437lm
ORDL136-25WA60	25W	60°	2396lm




Protection: IP65/IK07  
 Weight: 0.61KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo




Code	Watt(w)	Optic	Flux(lm)
ORDL158-36WA10	36W	10°	2843lm
ORDL158-36WA15	36W	15°	3594lm
ORDL158-36WA24	36W	24°	3601lm
ORDL158-36WA38	36W	38°	3537lm
ORDL158-36WA60	36W	60°	3495lm



Protection: IP65/IK07  
 Weight: 0.86KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo




Code	Watt(w)	Optic	Flux(lm)
ORDL180-45WA10	45W	10°	3554lm
ORDL180-45WA15	45W	15°	4495lm
ORDL180-45WA24	45W	24°	4501lm
ORDL180-45WA38	45W	38°	4437lm
ORDL180-45WA60	45W	60°	4395lm




Protection: IP65/IK07  
 Weight: 1.1KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo

# 防水筒灯


## Outdoor downlight




Code	Watt(w)	Optic	Flux(lm)
ORDL100-F15WA10	18W	10°	1185Lm
ORDL100-F15WA15	18W	15°	1495Lm
ORDL100-F15WA24	18W	24°	1502Lm
ORDL100-F15WA38	18W	38°	1439Lm
ORDL100-F15WA60	18W	60°	1396Lm




Code	Watt(w)	Optic	Flux(lm)
ORDL136-F25WA10	28W	10°	1973Lm
ORDL136-F25WA15	28W	15°	2496Lm
ORDL136-F25WA24	28W	24°	2502Lm
ORDL136-F25WA38	28W	38°	2437Lm
ORDL136-F25WA60	28W	60°	2396Lm




Protection: IP65/IK07  
 Weight: 0.4KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo




Protection: IP65/IK07  
 Weight: 0.61KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo




Code	Watt(w)	Optic	Flux(lm)
ORDL158-F36WA10	36W	10°	2843Lm
ORDL158-F36WA15	36W	15°	3594Lm
ORDL158-F36WA24	36W	24°	3601Lm
ORDL158-F36WA38	36W	38°	3537Lm
ORDL158-F36WA60	36W	60°	3495Lm



Code	Watt(w)	Optic	Flux(lm)
ORDL180-F45WA10	48W	10°	3554Lm
ORDL180-F45WA15	48W	15°	4495Lm
ORDL180-F45WA24	48W	24°	4501Lm
ORDL180-F45WA38	48W	38°	4437Lm
ORDL180-F45WA60	48W	60°	4395Lm



Protection: IP65/IK07  
 Weight: 0.86KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo



Protection: IP65/IK07  
 Weight: 1.1KG  
 Physical properties: Surface temperature below50 °C  
 Optional color temperature: singlewhite, RGBW  
 Standard driver: AC220V  
 Optional driver: external DMX512,0-10V,DALI, thyristo